

PELAPATATE 5KG
POTATO PEELER 5 KG RANGE



• Macchinario per uso professionale • Struttura completamente in acciaio inossidabile AISI 304 • Motore asincrono ventilato di produzione nazionale • Pareti abrasive facilmente sostituibili senza l'utilizzo di attrezzi • Elettrovalvola elettronica per ingresso acqua • Micro al coperchio e sportello • Coperchio in plastica trasparente infrangibile • Coperchio in acciaio inox (a richiesta) • Cassetto filtro allo scarico di serie • Visibili e pratici comandi digitali • Apparato elettrico esterno protetto da scatola di plastica isolata • Timer digitale multifunzione • Collettore di scarico a terra o parete • Trasmissione a cinghia • Norme CE • Fabbricato in Italia

• Professional equipment • Entirely structured in AISI 304 s/steel • Ventilated asynchronous Italian make motor • Abrasives designed to enable the user to operate, clean and maintain with the minimum of effort • Water jets electronic valve • Safety micro switch assembled on the cover and chute • Unbreakable transparent plastic cover • Waste filter drawer included • Digital and user-friendly control panel • Electric parts covered by safety ergonomic plastic case • Multifunction digital timer • Wall or floor discharge outlet • Belt transmission • CE approved • Proudly Made in Italy

DA BANCO
BENCHTOP MODEL



Collettore scarico laterale
Side discharge manifold (mm)
Ø 50



Peso netto
Net weight (kg)
26,0 kg



Dimensioni prodotto
Product dimension (mm)
B. 530 / D. 530 / H. 530

Dimensione imballo
Packing dimensions (mm)
B. 600 / D. 660 / H. 740



CON PIEDI
WITH BLACK LEGS



Collettore scarico inferiore
Lower discharge manifold (mm)
Ø 50



Peso netto
Net weight (kg)
30,0 kg



Dimensioni prodotto
Product dimension (mm)
B. 530 / D. 530 / H. 660

Dimensione imballo
Packing dimensions (mm)
B. 600 / D. 660 / H. 800



SUPPORTO STANDARD
CON CASSETTO E FILTRO INCLUSO
INCLUSIVE OF WASTE FILTER DRAWER



Collettore scarico inferiore
Lower discharge manifold (mm)
Ø 40



Peso netto
Net weight (kg)
34,0 kg



Dimensioni prodotto
Product dimension (mm)
B. 530 / D. 530 / H. 720

Dimensione imballo
Packing dimensions (mm)
B. 660 / D. 600 / H. 800



SUPPORTO ALTO
CON CASSETTO E FILTRO INCLUSO
WITH HIGH STAND INCLUSIVE OF WASTE FILTER DRAWER



Collettore scarico inferiore
Lower discharge manifold (mm)
Ø 50



Peso netto
Net weight (kg)
38,0 kg



Dimensioni prodotto
Product dimension (mm)
B. 530 / D. 530 / H. 970

Dimensione imballo
Packing dimensions (mm)
B. 600 / D. 660 / H. 1020



	NORME CE / CE APPROVED		SENZA NORME CE / NON CE APPROVED	
	Trifase / Three phase V. 230/400	Monofase / Single phase V. 230	Trifase / Three phase V. 230/400	Monofase / Single phase V. 230
5 KG BANCO 0,37 Kw (0,50 Hp) codice prodotto product code	FP105	FP104	FP105E	FP104E
5 KG CON PIEDI 0,37 Kw (0,50 Hp) codice prodotto product code	FP107P	FP106P	FP107PE	FP106PE
5 KG SUPPORTO STANDARD 0,37 Kw (0,50 Hp) codice prodotto product code	FP107	FP106	FP107E	FP106E
5 KG SUPPORTO ALTO 0,37 Kw (0,50 Hp) codice prodotto product code	FP109	FP108	FP109E	FP108E
CI supplemento per coperchio inox optional for stainless steel lid	su richiesta / on request		su richiesta / on request	
CF cassetto e filtro optional for drawer-filter	di serie / included		La versione non CE di base non prevede cassetto e filtro	Non Ce approved model is not inclusive of waste filter drawer

	Alimentazione Power supply (Volt/Hz)	Potenza Motor power (Kwatt/ Hp)	Giri piatto Peeler dish revolutions (RPM)	Produzione oraria Production per hour (kg/h)	Tempo ciclo pulitura Peeling cycle (sec)	Carico massimo Maximum charge (kg)	Temperatura acqua Water temperature (°C)	Alimentazione tubo flessibile Flexible pipe feeding (inch)	Collettore scarico laterale Side discharge manifold (mm)
5 KG	230/50 230-400/50	0,37 (0,50)	270	150	60-90	5	5-20	3/4	Ø50

